



NO-SLIP

SLIP RESISTANT COATING



Description: A slip resistant epoxy coating that cures to a hard, flat, textured finish. Designed for interior and exterior use on concrete, steel, wood, fiberglass, aluminum, tile, etc. Particularly effective anywhere water or other slippery conditions exist. Contains a synthetic grit with no sharp edges. Perfect for use on irregular shapes or anywhere "grit-tape" would not be feasible. Easy to use one part aerosol eliminates mixing, waste, clean-up and application of separate grit.

Directions: EASY TO APPLY • SETS UP QUICKLY.
AVAILABLE IN: CLEAR, GREY, OSHA YELLOW, BLACK AND WHITE.
SOME COLORS ARE AVAILABLE ONLY ON SPECIAL ORDER.

Advantages: MORE EFFECTIVE THAN GRIT • LASTS LONGER • NO TEAR AWAY
EASY TO REAPPLY • GREAT ADHESIVE

Where to Use: APARTMENT BUILDINGS • HOSPITALS • NURSING HOMES • SHIPPING OPERATIONS
INDUSTRIAL PLANTS • MUNICIPALITIES • SCHOOLS • OFFICES • WAREHOUSES
MARINAS • MACHINE SHOPS • GARAGES • CONSTRUCTION COMPANIES
RESTAURANTS • HOTELS • CONDOS

Recommended For: STEPS • LADDERS • RAMPS • PUBLIC RESTROOMS • LOADING DOCKS
MARINE DOCKS • AROUND INDUSTRIAL EQUIPMENT • BOATS
RUNNING BOARDS • STEP PADS • POOLS DECKS • DIVING BOARDS

Specifications:

APPEARANCE AND ODOR.....	Colored Liquid / Solvent Odor
FLASH POINT OF CONCENTRATE	45°F T.O.C.
FLAMMABILITY	Extremely Flammable Spray
SPECIFIC GRAVITY	0.800
PROPELLANT.....	Hydrocarbon
SPRAY PATTERN.....	Coarse Circular Fan Spray
NFPA FIRE RATING.....	Level 3 Aerosol
PACKAGING.....	12 x 12oz. Net Wt. Cans per case (16oz. Cans)

